

AUSTRAL CROCPLY to be used/installed as specified.

Plywood to be manufactured with timber species: **Araucaria (Hoop Pine) with phenolic faces.**

Core grade to be **A Multiply**, conforming to Australian Standards for veneer grading.

Glue system to be used is **A-Bond Phenolic (black glueline)** with formaldehyde emissions rating of **E0**, tested in accordance with AS/NZS 2098.11 : 2005. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2272:2006** and be certified under the **EWPA JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Plywood to conform to Stress Grade **F22-F27** (or better), in accordance with AS/NZS 2269.1.

Panel size to be **2440 x 1220mm** (delete as required).

Panel thickness to be **12, 15, 18, 24mm** (delete as required).

Panels to be prefinished in **Mesh pattern face with smooth back, Smooth both sides** (delete as required).

<http://www.australply.com.au/austral-crocply>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666



**AUSTRAL
PLYWOODS**

07 3426 8666
sales@australply.com.au
www.australply.com.au

*100% Australian
made, since 1925*