



TECHNICAL INFORMATION SHEET

Group 1 Fire Rated Interior Panel

IMPORTANT – Before using this product you **must** read the safety data sheet

Use: Austral FireHoop is a fire rated decorative panel designed for walls and ceiling linings and must only be used in interior applications. FireHoop is supplied either as a solid or acoustic panel. The acoustic panel is perforated with 8mm holes and 32mm centres either in square or offset pattern with a 30mm border. Acoustic panels are backed with a fire rated acoustic backing material.

Material: Austral FireHoop consists of a magnesium oxide core with high pressure laminate face and back. Austral FireHoop is deemed non-hazardous according to Safe Work Australia criteria. Austral FireHoop panel contains magnesium chloride and may corrode metal work if not installed correctly or used in wet or high humidity areas.

Care: Austral FireHoop is a decorative panel and must be handled with care. Austral FireHoop must remain dry and stored in a protected area. Before installation, store Austral FireHoop on a flat, dry surface with a cover sheet on top. Do not store FireHoop panels on their edge as this may cause bowing or damage to the edge. Avoid direct sunlight, wind, rain and humidity, all of which can affect the appearance and performance of the panel.

Handling & Cutting: Use PVC or rubber gloves and dust proof goggles when handling. Use a diamond blade when cutting Austral FireHoop and always wear safety glasses. Operators must avoid dust inhalation and cut only in a well ventilated area, use mechanical extraction and wear a class P1 respirator. Use a fine sandpaper minimum 320 grit to clean up any sharp edges.

Mandatory Personal Protective Equipment



Gloves



Glasses



P1 Respirator