

Wording to assist in writing a specification for Austral Plywoods plywood products

ARIAPLY to be used/installed as specified.

Plywood to be manufactured with timber species: **Hoop Pine (Araucaria Cunninghamii)**.

Face and back veneer grades to be **AC**, conforming to Australian Standards for veneer grading.

Core grade to be **D**, conforming to Australian Standards for veneer grading.

Glue system to be used is **A-Bond Phenolic (black glueline)**. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2271:2004** and be certified under the **EWPA JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Plywood to be certified Fire Group **3** per BCA Specification C1.10 clause 4.

Panel size to be **2400 x 1200mm** (delete as required).

Panel thickness to be **9.5, 12.5mm** (delete as required).

Panels to be installed with **shadowFIX, X-Tack** (delete as required) in accordance with installation instructions.

Panels to be prefinished in **Natural Hoop, Blackbutt, Spotted Gum, Jarrah, Walnut, Ebony, Ash** (delete as required). Manufacturer warranty on coating to be 7 years.

<http://www.australply.com.au/ariaply>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666



**AUSTRAL
PLYWOODS**

07 3426 8666
sales@australply.com.au
www.australply.com.au

*100% Australian
made, since 1925*