

Wording to assist in writing a specification for Austral Plywoods plywood products

AUSTRAL CROCPLY to be used/installed as specified.

Plywood to be manufactured with timber species: **Araucaria (Hoop Pine) with phenolic faces**.

Core grade to be **A or D**, conforming to Australian Standards for veneer grading.

Glue system to be used is **A-Bond Phenolic (black glueline)** with formaldehyde emissions rating of **E0**, tested in accordance with AS/NZS 2098.11 : 2005. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2272:2006 or AS/NZS 2269:2012** and be certified under the **EWPAAS JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Plywood to conform to Stress Grade **F22 - F27** (or better), in accordance with AS/NZS 2269.1.

Panel size to be **2400 x 1200, 2440 x 1220mm** (delete as required).

Panel thickness to be **13, 17, 19, 25mm** (delete as required).

Panels to be prefinished in **Mesh pattern face with smooth back, Smooth both sides** (delete as required).

Option: **Marine core or Structural core** (delete as required).

<http://www.australply.com.au/austral-crocply>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666