

Wording to assist in writing a specification for Austral Plywoods plywood products

---

**AUSTRAL LASERPLY** to be used/installed as specified.

Plywood to be manufactured with timber species: **Hoop Pine (Araucaria Cunninghamii)**.

Face and back veneer grades to be **AA**, conforming to Australian Standards for veneer grading.

Core grade to be **A**, conforming to Australian Standards for veneer grading.

Glue system to be used is **C-Bond MUF (white glueline)** with formaldehyde emissions rating of **E0**, tested in accordance with AS/NZS 2098.11 : 2005. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2270:2006** and be certified under the **EWPA JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Plywood to be certified Fire Group **3** per BCA Specification C1.10 clause 4.

Panel size to be **2400 x 1200mm** (delete as required).

Panel thickness to be **3, 4, 5, 6.5, 9, 12.5, 16, 19, 25, 32mm** (delete as required).

<http://www.australply.com.au/austral-laserply>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666



**AUSTRAL  
PLYWOODS**

07 3426 8666  
sales@australply.com.au  
www.australply.com.au

*100% Australian  
made, since 1925*