

Wording to assist in writing a specification for Austral Plywoods plywood products

AUSTRAL SLAT PANEL to be used/installed as specified.

Plywood to be manufactured with timber species: **Hoop Pine (Araucaria Cunninghamii)**.

Core grade to be **A**, conforming to Australian Standards for veneer grading.

Glue system to be used is **C-Bond MUF (white glueline)** with formaldehyde emissions rating of **E0**, tested in accordance with AS/NZS 2098.11 : 2005. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2270:2006** and be certified under the **EWPA JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Panel size to be **2400 x 1200mm** (delete as required).

Panel thickness to be **15mm** (delete as required).

Panels to be installed with **Direct screw fix** (delete as required) in accordance with installation instructions.

Option: **Solid or Acoustic (13.9% open area)** (delete as required).

<http://www.australply.com.au/slatpanel>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666



**AUSTRAL
PLYWOODS**

07 3426 8666
sales@australply.com.au
www.australply.com.au

*100% Australian
made, since 1925*